



TUMC 500 - 550 - 600 - 1000

Tank Optic Fibre Distribution and Termination Unit

Application

The TUMC 500, 550, and 600 are designed for cabinet and remote termination applications in UMC^s, DLU^s, OFDC^s, Cellular and Telecommunication masts sites.

The TUMC 1000 is designed for 19" and 21" racks in cabinets and termination line bays.

The TUMC 500, 550 and 600 can accommodate 12 Fibre Optic Terminations, while the TUMC 1000 can accommodate both 12, 24 and 48 Fibre Optic Terminations. The Unit comes fitted with a splice organiser tray. Fitted splice organiser tray.

The middle alignment sleeve adapter plate is interchangeable to accommodate various types of fibre optic midcouplers. Mounting brackets are supplied.

Features

- Quick Installation
- Easily accessible
- Robust
- Interchangeable adaptor panels



TECHNICAL INFORMATION

DIMENSIONS:

MODEL	WIDTH	HEIGHT/LENGTH	DEPTH
TUMC 500	195	248 (L)	46
TUMC 550	195	248 (H)	46
TUMC 600	142	248 (H)	46
TUMC 1000	192	435 (L)	46

MATERIAL: Sheet metal

SURFACE FINISH: Grey RAL 7035

ORDERING INFORMATION:

